



# DYMO® Industrial Labels

Label it fast, label it once, label it right.



# Tough, jobsite-tested labels for industrial applications.

## Rely on DYMO® Industrial Labels.

DYMO® Industrial labels are tough – jobsite tested and UL recognized.

Thermal transfer printing means labels won't smudge, smear or fade.

Choose up to a 24 mm label width in a broad assortment of materials and colours that meet OSHA, ANSI, and ISO standards.

All DYMO® Industrial labels are distributed from an easy-to-load cartridge, and with a split-back design, peeling and applying is quick and easy.

DYMO® Industrial labels help you get labelling jobs done fast, and done right – the first time.



### DYMO® Industrial Labels are available in:

Flexible Nylon  
Permanent Polyester  
Indoor/Outdoor Vinyl  
Heat-Shrink Tube  
Non-Adhesive Tag  
Self-Laminating




Labels



## DYMO® Industrial Label Benefits:

- 1 Industrial-strength adhesives resist moisture, extreme temperatures, UV light and more – so labels won't curl or fall off
- 2 Available in a range of UL recognized materials for virtually every industrial labelling application; heat-shrink tubes tested to SAE, ASTM and military specifications
- 3 Thermal transfer printing technology – label text won't smudge, smear, or fade
- 4 Choose from 6, 9, 12, 19, and 24 mm label widths in a broad colour assortment that meet OSHA, ANSI, and ISO standards
- 5 Easy-to-peel split back design makes applying labels quick and easy

# The right label for virtually every situation and surface.



## Indoor/Outdoor Vinyl

For general labelling or extreme conditions. Vinyl labels offer moisture, chemical and UV resistance, making them ideal for labelling both indoors and outdoors. Available in the widest range of colours that adhere to OSHA, ANSI and ISO colour standards.

UL recognized as a component to UL 969

## Flexible Nylon

For labelling wires, cables and rounded surfaces. Flexible Nylon labels conform and stick tightly to wires, cables, curved and textured surfaces. Tear-proof material resists damage when pulled through tight spaces or conduits.

UL recognized as a component to UL 969

## Permanent Polyester

For labelling panels, blocks, faceplates, shelves, bins, beams and more. Permanent Polyester labels have a polished finish that leaves your work looking professional. Available in smaller widths that fit most patch panels, blocks and other distribution panels.

UL recognized as a component to UL 969

## Heat-Shrink Tube

For high-end cable identification. A 3:1 shrink ratio helps ensure a secure fit on wires and cables. Print directly on Heat-Shrink Tubes with any DYMO® Industrial labelling tool.

Meets MIL-M-81531, MIL-STD-202G, SAE-DTL- 23053/5 (Class 1 & 3)  
UL recognized as a component to UL 224

## Non-Adhesive Tag











For sliding into racks or faceplates that do not require adhesive. Made from polyester for increased durability.

## Self-Laminating

Self-Laminating labels protect your printed area from exposure to oil, solvents, water and abrasion when applied to wires and cables.


All DYMO® Industrial labels are RoHS compliant.

## How to choose the right DYMO® Industrial label:

ENVIRONMENT	 Heat/Cold Resistant	 UV Light Resistant	 Oil Resistant	 Water Resistant	 Chemical Resistant	 Colour Coding
 <b>Cable/Wire</b>	Flexible Nylon Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl
 <b>Curved Surface</b>	Flexible Nylon Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl Flexible Nylon	Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl Flexible Nylon	Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl
 <b>Flat Surface</b>	Permanent Polyester Flexible Nylon	Permanent Polyester Indoor/Outdoor Vinyl	Permanent Polyester Indoor/Outdoor Vinyl	Permanent Polyester Indoor/Outdoor Vinyl	Permanent Polyester Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl
 <b>Textured Surface</b>	Permanent Polyester Flexible Nylon	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl

Top = Best Option Bottom = Alternate Option

# Available DYMO® Industrial label widths and colours:



IND	LABEL APPLICATIONS	LABEL COLOUR	6 mm	9 mm	12 mm	19 mm	24 mm
<b>Labels that stick and stay stuck.</b> DYMO® Industrial labels are tough— jobsite tested and UL recognized. Labels won't smear or fade and are built with industrial-strength adhesives to resist moisture, UV light and extreme temperatures. Whether you are labelling to OSHA, ISO and ANSI colour standards or labelling in harsh conditions, DYMO® Industrial labels have you covered. DYMO® Industrial labels are designed to work exclusively with Rhino™ printers and to perform on a variety of surfaces.  <a href="http://www.dymo.com/industrial">LEARN MORE: www.dymo.com/industrial</a>	<b>BLACK ON WHITE</b> – 18443 <i>S0718580</i>	18444 <i>S0718600</i>	18445 <i>S0718620</i>	1805430			
		<b>BLACK ON YELLOW</b> – 18432 <i>S0718450</i>	18433 <i>S0718470</i>	1805431			
		<b>BLACK ON ORANGE</b> – 18435 <i>S0718490</i>	18436 <i>S0718500</i>	1805427			
		<b>BLACK ON GREY</b> – 1805413	1805419	1805425			
		<b>WHITE ON RED</b> – 1805416	1805422	1805429			
		<b>WHITE ON BLACK</b> – 1805437	1805435	1805436	1805432		
		<b>WHITE ON GREEN</b> – 1805414	1805420	1805426			
		<b>WHITE ON BLUE</b> – 1805243	1805417	1805423			
<b>VINYL</b> Length 5.5 m - UL Recognized Component to UL969 - RoHS compliant 	<b>WHITE ON PURPLE</b> – 1805415	1805421	1805428				
	<b>WHITE ON BROWN</b> – 1805412	1805418	1805424				
<b>PERMANENT POLYESTER</b> Length 5.5 m - UL Recognized Component to UL969 - RoHS compliant 	<b>BLACK ON WHITE</b> 1805442 18482 <i>S0718240</i>	18483 <i>S0718210</i>	18484 <i>S0718220</i>	1734523 <i>S0773830</i>			
	<b>BLACK ON CLEAR</b> 1805440 18508DMO <i>S0718160</i>	622289	622290	1805433			
	<b>BLACK ON METALLIC</b> 1805441 18485 <i>S0718170</i>	18486 <i>S0718180</i>	18487 <i>S0718200</i>	1805434			
<b>HEAT SHRINK TUBES</b> Length 1.5 m - UL Recognized Component to UL224 - Meets MIL-STD-202G, MIL-M-81531 & SAE-DTL 23053/5 (Class 1 & 3) - RoHS compliant 	<b>BLACK ON WHITE</b> 18051 <i>S0718260</i>	18053 <i>S0718280</i>	18055 <i>S0718300</i>	18057 <i>S0718330</i>	1805443		
	<b>BLACK ON YELLOW</b> 18052 <i>S0718270</i>	18054 <i>S0718290</i>	18056 <i>S0718310</i>	18058 <i>S0718340</i>	1805444		
<b>FLEXIBLE NYLON</b> Length 3.5 m - UL Recognized Component to UL969 - RoHS compliant 	<b>BLACK ON WHITE</b> – 18488 <i>S0718100</i>	18489 <i>S0718120</i>	1734524 <i>S0773840</i>				
	<b>BLACK ON YELLOW</b> – 18490 <i>S0718080</i>	18491 <i>S0718090</i>	1734525 <i>S0773850</i>				
<b>NON-ADHESIVE TAG</b> Length 5.5 m - RoHS compliant 	<b>BLACK ON WHITE</b> 18111 <i>S0718350</i>	18113 <i>S0718380</i>	–	–			
<b>SELF-LAMINATING</b> Length 5.5 m - RoHS compliant 	<b>BLACK ON WHITE</b> – 1734821 <i>S0773860</i>	–	–	–			