

## SWA Steel Wire Armoured Cable 3 Core

---

Steel Wire Armoured Cable cut to length with discounted prices specific to length required.

Armoured XLPE mains cable to British Standard BS5467 suitable for power networks.



**Steel Wire Armoured Cable cut to length with discounted prices specific to length required.**

**Armoured XLPE mains cable to British Standard BS5467 suitable for power networks.**

Specification:

- Current rating: 124 Amp
  - 6943XL 25mm 3 - Core SWA Cable
  - Multi-Core XLPE insulated/PVC/SWA/PVC sheathed to BS5467 600/1000V
  - Conductors: Plain annealed stranded copper
  - Insulation: XLPE (Cross linked polyethylene)
  - Core identification: 2 core (Brown & Blue), 3 core (Brown, Black & Grey), 4 core (Brown, Black, Grey & Blue). 5 core & above - white core with black numbers.
  - Bedding: PVC (Polyvinyl-Chloride)
  - Colour: Black
  - Voltage: 600/1000V
  - Operating temperature: Max 90°C, min bending 0°C Standard: BS5467: Electric cables. Thermo-setting insulated, armoured cables for voltages of 600/1000V and 1900/3300V
- Designed for use in mains supply electricity. These cables are provided with mechanical protection and are therefore suitable for external use and direct burial.