

**High Temperature Hose & Pipe Protection Fire
Resistant Glass Fibre Webbing Tape. 50.0mm x 3.0
thickness. White.**

HILFLEX-FGT-50.0-3.0-9-CLS



HILFLEX High Temperature Hose & Pipe Protection Fire Resistant Glass Fibre Webbing Tape is manufactured from texturised fibreglass yarns which offers superior insulating properties.

Extremely hard wearing and versatile.

Protects Industrial hydraulic hoses and lines, pneumatic lines, fuel & oil lines, brake lines, wires, cables, tubes & pipes from exposure to high and extreme heat conditions.

The tape is overlapped by 50% when wrapping, which provides added stability. Safetywire, clamps, pure silicone tape or Cable ties can be used to secure the tape firmly in place after installation.

Use in conjunction with our Stainless-Steel cable ties or Silicone Tape for a secure fastening.

Features & Benefits:

Provides temperature and abrasion resistance

Melting Point: +550°C

Flammability VW-1

Overlapped by 50% when wrapping, which provides added stability.

Material: Woven Fibreglass

50mm x 3mm

White



We recommend using with our Heavy Duty Stainless Steel Cable Ties. Hilltop's uncoated cable ties are manufactured from 316 stainless steel, have a high tensile strength and are fireproof and halogen free. They are available in a range of sizes.

HTP-SSTR1-CABLE-TIE

High Temperature Hose & Pipe Protection Fire Resistant Glass Fibre Webbing Tape. 50.0mm x 3.0 thickness. White.

**High Temperature Hose & Pipe Protection Fire
Resistant Glass Fibre Webbing Tape. 50.0mm x 3.0
thickness. White.**

HILFLEX-FGT-50.0-3.0-9-CLS

Technical Datasheet

Material	Fibreglass
Flammability	VW-1
Melting point	+550°C
Standard colour	White
Standard thickness	1.5mm
Cutting tool	Scissors



High Temperature Hose & Pipe Protection Fire Resistant Glass Fibre Webbing Tape. 50.0mm x 3.0 thickness.
White.