

PTFE White Tape—12mm x 12mtrs



Product Description

Water grade PTFE thread seal tape. (Polytetrafluoroethylene 100% Raw Polymer)

Applications

Commonly used in the plumbing & heating industries for sealing pipe threads such as Water and Propylene Glycol, Kerosene and Diesel.

Features & Benefits

Non-adhesive no need for messy compounds
Won't harden or dry out
Air & watertight seal
Impermeable to >7bar
Resistant to cracking
Performs a lubricating function

Technical Performance

Description	Units	Value
Tape thickness	mm	0.076 ±10%
Temperature	°c	-60 to +260
Specific weight	gr/cm ³	2.13 – 2.23
Pressure	Bar	7

Declaration of Conformity Information

BS 7786:2006 Grade L EN-751-3:1997
DIN30660
WRAS Approval 1306504
Methane Screwed Fittings up to 300Bar pressure
Sulphuric Acid 30%

REACH SVHC Status – NO SHVC present according to candidates list of 15th June 2015

RoHS Compliance Status – Yes

Storage Details

Shelf life recommended 1 year from date of despatch at the moderate temperature and humidity environment.

Hilltop Products Ltd

Kirkstead Way
Golborne
Warrington, WA3 3PY

www.hilltop-products.co.uk

Tel: 01942 723101

Fax: 01942 273817

Email: sales@hilltop-products.co.uk