
LSTT

Single Wall tube. A Premium grade heat shrink tube primarily used for electrical insulation. Available in several colours.



PRODUCT DIMENSIONS

SIZE	Inside Diameter as supplied (min) mm <i>(inch)</i> D	Inside Diameter after recovery (max) mm <i>(inch)</i> d	Wall Thickness after recovery (nom) mm (inch) W	Wall Thickness Tolerance after recovery mm <i>(inch)</i>	
1.6	1.6 (.063)	0.8 (.031)	0.50 <i>(.018)</i>	0.12 (.005)	
2.4	2.4 (.093)	1.2 (.046)	0.55 <i>(.022)</i>	0.12 (.005)	
3.2	3.2 (.125)	1.6 (.063)	0.55 <i>(.022)</i>	0.12 (.005)	
4.8	4.8 (.187)	2.4 (.093)	0.55 <i>(.022)</i>	0.12 (.005)	
6.4	6.4 (.250)	3.2 (.125)	0.65 <i>(.026)</i>	0.15 (.006)	
9.5	9.5 <i>(.375)</i>	4.8 (.187)	0.65 <i>(.026)</i>	0.15 (.006)	
12.7	12.7 (.500)	6.4 (.250)	0.65 <i>(.026)</i>	0.15 (.006)	
19.0	19.0 <i>(.748)</i>	9.5 <i>(.375)</i>	0.80 (.032)	0.15 (.006)	
25.4	25.4 (1.000)	12.7 (.500)	0.95 <i>(.037)</i>	0.18 (.007)	
32.0	32.0 (1.260)	16.0 <i>(.630)</i>	1.05 (.041)	0.20 <i>(.008)</i>	
38.0	38.0 (1.496)	19.0 <i>(.748)</i>	1.05 (.041)	0.20 <i>(.008)</i>	
52.0	0 52.0 (2.047) 26.0 (1.024)		1.14 (.045) 0.18 (.007)		

LSTT – STANDARD SIZE REFERENCE DIMENSIONAL DRAWING							
			©2020 TI		TE Connectivity Ltd. family of companies All Rights Reserved		
				DIMENSIONS IN	TITLE		
				mm <i>(Inch)</i>	LSTT	- IRRADIATED MODIFII	ED
				$\bigcirc \bigcirc \bigcirc \bigcirc$	POLYOLEF	IN SINGLE WALL HEAT TUBING	SHRINK
A 4			01/04/0001	SHEET	NO		REV
A1	Minor text change.	HD	21/04/2021	1 of 2	I STT -	Standard sizes	A1
REV	ENGINEERING CHANGE	CHK	DATE	1012		otanidara Sizes	AI

LSTT

PRODUCT INFORMATION

General use single wall Polyolefin Tubing. Shrink Ratio - 2:1 Longitudinal Shrinkage on full recovery – 0 to -10% Material conforms to TE Specification RW-2051 Standard Colours: Black, White, Red, Blue, Yellow, Clear Non-Standard Colours: Brown, Orange, Green, Violet, Grey Non- Flame Retardant

Tubing cut to specific lengths can be supplied from the product sizes referenced within this drawing.

STANDARD CUTTING TOLERANCES (mm)				
CUT LENGTH	TOLERANCE			
Up to 9.9mm	±0.5mm			
10mm to 24.9mm	±1.0mm			
25mm to 54.9mm	±1.5mm			
55mm to 99.9mm	±3.0mm			
100mm to 149.9mm	±4.0mm			
150mm to 499.9mm	±5.0mm			
500mm to 1200mm	±12.5mm			

Cut length tolerances are as per the following table:



SHEET

REV