

**LK2A**

**111-60119**



T18S – T150XL



Available in a wide range of materials, these cable ties all feature internal serrations allowing for a positive hold onto cable, hose and pipe bundles. The design of the head guarantees a high tensile strength whilst allowing a very low insertion force, this, combined with the bent tail design of many of the ties ensures a simple and quick installation. Whilst easily installed by hand manual, and pneumatic (for high volume applications) tensioning tools are available to ensure a consistent and safe installation.

For routing, bundling and securing of cables, pipes and hoses.

## Base Data

### Colour

Natural (NA)

### Label E-Number Finland

13 704 21

### Package Content

100

### Quantity (Sold Unit / EDP)

100

### Recommended Application Tool

MK3SP, MK3PNSP2, MK7P, MK7, MK7HT, MK20, MK6, MK6PN, MK9, MK9HT, MK21

## Logisitic and Packaging

### Carton Quantity

6000

### EAN code

4031026106847

### Quantity of Europallet

108000

### Weight (kg) (Metric)

1.1 kg

## Material and Specifications

### Flammability

UL94 V2

### Material

Polyamide 6.6 (PA66)

### Material Shortcut

PA66

### Operating Temperature (Metric)

-40 °C to +85 °C Continuous, (+105 °C for 500 h)

## Product Dimensions

### Bundle Diameter max (Metric)

73

### Bundle Diameter min (Metric)

5

### Length L (Metric)

270

### Minimum Tensile Strength (N)

225

### Width W (Metric)

4.6