

## Spiral Guard® FRAS—Spec Sheet

### Specifications

- Flame retardant anti-static spiral guard.
- Tested and approved in accordance with the former British coal specification 182: 1986, satisfying the requirements of the non metallic scheme for use underground.
- Tested and approved by Mine Safety Laboratory Department of Mineral Resources. NSW to AS2660 Fras Compliance—1991.
- International Standard : ISO 6805.



Hose protection focused on reducing expensive down-time costs and increasing site safety.

Part	I/D	Wrap Range	Hose I/D	1-wire	2-wire	Multi-spiral	Dash Size	Quantity
16mm	13	13-17mm	1/4"	Yes	Yes	-	-4	20m
20mm	16	16-22mm	1/4"	-	Yes	-	-4	20m
25mm	21	22-28mm	1/2"	Yes	Yes	Yes	-8	20m
32mm	27	27-33mm	5/8"	Yes	Yes	Yes	-10	20m
40mm	33	33-44mm	1"	Yes	Yes	Yes	-16	20m
50mm	44	44-65mm	1 1/4"	Yes	Yes	Yes	-20	20m
75mm	65	65-90mm	2"	Yes	Yes	Yes	-32	20m
90mm	80	Hose Looms 80mm—200mm						20m

### Characteristics:

- Suitable for the protection of most types of hydraulic, pneumatic and industrial hose assemblies.
  - The only plastic hose protection to be cut from pipe.
- Lightweight protection reducing the weight / stress of hydraulic hose.